

Data Sheet

Multi-Cassette Currency Dispenser

Fujitsu F510

Fast and reliable dispensing with F510

Designed for applications that require high volume, Fujitsu's F510 media dispenser offers state-of-the-art reliability and high capacity. With on-board diagnostics and front, rear or dual service configurations, the F510 reduces support costs and minimizes maintenance. The Fujitsu F510 is one of the most advanced media dispensers on the market today, with the speed, capacity, reliability, and advanced diagnostics for the most demanding environments. At seven notes per second, the F510 is one of the fastest cash dispensers in the industry. Despite its advanced features, the F510 has been designed to drive down total cost of ownership. The unit features advanced on-board and remote diagnostics to help detect problems before they occur, and its integrated reject bin reduces maintenance needs.



Key Features

- Configurable for up to six cassettes
- On-board diagnostics tools detects issues before they occur
- Maximum cassette flexibility in limited vertical space
- Large capacity means less maintenance required
- Adjustable bill low sensor adapts to deployer's needs
- Reliably dispense mixed new and used notes
- Industry-leading Fujitsu parts for simplified support

The Fujitsu F510 is built upon the foundation Fujitsu has created over 30 years of designing media dispensing devices of legendary quality. Backed by Fujitsu's team of dedicated professionals, the Fujitsu F510 provides OEMs and integrators with the flexibility and reliability needed for demanding note-dispensing applications. The unit is expandable up to six cassettes, with each cassette capable of supporting up to 3,000 new notes. With a total capacity of 18,000 new notes, the Fujitsu F510 is the premier solution for high-volume locations and anywhere dispensing of media is required.

Fujitsu F510 Specifications

Dimensions (W x D x H)	280mm x 763mm x 405mm (2 denominations)
Weight (w/o media)	72kg
Temperature	Operating: 0°C - 40°C Non-operation: -5°C - 50°C
Humidity	Operating: 10% - 85% Non-operating: 8% - 95%
Maximum Capacity per Cassette	3,000 new notes (approx.)* 370mm
Maximum Dispense	60 notes per transaction
Service Area	Front, rear or dual
Number of Cassettes	1-6 cassettes
Reject Area Capacity	150 notes
Acceptable Media Range	Max. (mm) 82mm x 172mm Min. (mm) 60mm x 120mm
Thickness	0.7 ~ 0.3
Processing Speed	7 notes per second
Interface	RS232C
Electrical Requirements	DC +24V +/- 10% Avg. 4A Peak 10A
Compliance	RoHS, UL

Fujitsu Frontech North America reserves the right to change specifications without notice

**Actual number of notes depends on fitness of currency, new versus used*



Contact Fujitsu Frontech North America

Address: 36 Technology Dr, Suite #150, Irvine, CA, 92618

Phone: 877-766-7545

Email: FNAsales@fujitsu.com

Website: fujitsufrontechna.com/fujitsu-f510



©2023 Copyright Fujitsu Frontech North America Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks. All other trademarks are the property of their respective owners. Statements herein are based on normal operating conditions and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America Inc. reserves the right to modify, at any time without notice, these statements, our services, products, and their warranty and performance specifications.