

Data Sheet

Multi-Cassette Currency Dispenser

Fujitsu F56

Make note dispensing a snap with F56

The Fujitsu F56 currency dispenser answers the call to provide fast, large-capacity note dispensing in a compact design. Building on more than 30 years of experience in creating media-dispensing devices of the highest quality, the Fujitsu F56 offers many features usually found only on more expensive units. It can be configured to be serviced from the front or rear, making installation and integration by OEMs a snap. With multiple delivery options, like semi-bunch, presenter, bulk transports and custom transports, the F56 allows deployers to customize and differentiate their cash delivery programs. The F56 can hold its own when it comes to capacity. When OEMs and integrators need a reliable, high-capacity note dispenser in a small size, the Fujitsu F56 is the obvious choice.



Key Features

- Multitude of delivery options, including through the wall
- On-board diagnostics tools resolves issues fast
- Compact size allows for maximum flexibility
- Large capacity means less maintenance
- Additional demonination options for large capacity applications
- High-end features at an affordable cost
- Flexible design adapts to numerous application possibilities

Designed for maximum flexibility, the Fujitsu F56 can be configured with up to six cassettes, each capable of holding up to 500 new notes. For added security, the cassettes can be configured with locks so they can be easily and safely transported by CIT companies. The F56 is capable of dispensing mixed new and teller fit, and mixed paper and polymer notes out of the same cassette. Enhanced features like bill low and denomination sensors ensure that you have cash at peak times and you are dispensing the correct denomination to your customers. The F56 eliminates downtime to improve your bottom line.

Fujitsu F56 Specifications

Dimensions (W x D x H)	160mm x 397mm x 375mm (2 denominations)
Weight (w/o media)	11kg
Temperature	Operating: 0°C - 40°C Non-operation: -5°C - 50°C
Humidity	Operating: 10% - 95% Non-operating: 8% - 95%
Maximum Capacity per Cassette	500 new notes (approx.*) 60mm
Maximum Dispense	20 notes per transaction
Service Area	Front and side service access
Read Sensitivity (Maximum)	-84 dBm
Number of Cassettes	2 standard, up to 6 optional
Reject Area Capacity	20 notes
Acceptable Media Range	Max. (mm) 82mm x 160mm Min. (mm) 60mm x 120mm
Thickness	0.9 ~ 0.3
Processing Speed	2 notes per second
Interface	RS232C
Electrical Requirements	DC +24V +/- 10% Avg. 4A Peak 7A
Compliance	RoHS, UL/TUV

Fujitsu Frontech North America reserves the right to change specifications without notice

**Actual number of notes depends on fitness of currency, new versus used*



Contact Fujitsu Frontech North America

Address: 36 Technology Dr, Suite #150, Irvine, CA, 92618

Phone: 877-766-7545

Email: FNAsales@fujitsu.com

Website: fujitsufrontechna.com/fujitsu-f56



©2023 Copyright Fujitsu Frontech North America Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks. All other trademarks are the property of their respective owners. Statements herein are based on normal operating conditions and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America Inc. reserves the right to modify, at any time without notice, these statements, our services, products, and their warranty and performance specifications.