

# Data Sheet

## Multi-Cassette Currency Recycler

### Fujitsu G750L

#### *High capacity and versatility*

The Fujitsu G750L bill recycling unit raises the bar when it comes to speed, capacity and reliability in a high-end currency management system for the OEM sales channel. Leveraging the same proven technology that is currently installed in thousands of Fujitsu ATMs worldwide, the Fujitsu G750L has the capacities and flexibility that many of smaller recyclers lack. The Fujitsu G750L supports provisional credit, which empowers your customer to credit accounts immediately, thereby improving cash flow and enhancing the bottom line. With greater capacities and flexibility, the Fujitsu G750L may be the ideal OEM solution for teller assist, ATMs, bill payment or front or back-office cash management systems. In other words, the G750L is suitable for virtually any environment that handles large sums of cash.



#### Key Features

- Configurable from two to six cassettes
- Flexibility for front or rear service
- Multiple delivery options like semi-bunch, tray, or bulk transport
- Field upgradeable to maximize capacity
- On-board diagnostics resolves issues quickly
- Simplified integration with RS232 or USB interface
- Industry-leading Fujitsu parts for simplified support

The Fujitsu G750L is the new standard for large-capacity cash recycling. Built for enhanced security and exemplary performance, the Fujitsu G750L is the ideal solution for high-end currency management. The innovative racked out design permits easy access to the cassettes to clear jams or foreign objects. The Fujitsu-patented BV is designed to protect your investment far into the future. With the introduction of new currencies, new polymer notes, and anti-counterfeiting measures, it is important you have the most flexible BV technology available. The Fujitsu G750L makes upgrades easy with no on-site visits required.

# Fujitsu G750L Specifications

Dimensions (W x D x H)	378mm x 725mm x 828mm
Weight (w/o media)	158kg
Temperature	Operation: 5°C - 50°C Stop State: -5°C - 50°C
Humidity	Operation: 20% - 80% Stop State: 10% - 90%
Maximum Deposit	200 Notes
Maximum Dispense	200 Notes
Recycle Stacker Capacity	2,700* Notes x 4 Cassettes; option 5 cassettes with no depository option
Deposit Cassette Capacity	3,000* Notes
Reject Bin Capacity	1,000* Notes
Acceptable Media Range	Max. (mm) 70mm x 156mm Min. (mm) 65mm x 140mm
Thickness (mm)	0.09 ~ 0.20
Processing Speed	8 notes/second
Interface Specifications	USB 2.0 Full Speed CEN / XFS
Electrical Requirements	DC +24V +/- 10% Avg.24.5A Peak 33.0A
Compliance	RoHS, UL

*Fujitsu Frontech North America reserves the right to change specifications without notice*

*\*Actual number of notes depends on fitness of currency, new versus used*



## Contact Fujitsu Frontech North America

Address: 36 Technology Dr, Suite #150, Irvine, CA, 92618

Phone: 877-766-7545

Email: [FNAsales@fujitsu.com](mailto:FNAsales@fujitsu.com)

Website: [fujitsufrontechna.com/fujitsu-g750l](http://fujitsufrontechna.com/fujitsu-g750l)



©2023 Copyright Fujitsu Frontech North America Inc. All rights reserved. Fujitsu and the Fujitsu logo are registered trademarks. All other trademarks are the property of their respective owners. Statements herein are based on normal operating conditions and are not intended to create any implied warranty of merchantability or fitness for a particular purpose. Fujitsu Frontech North America Inc. reserves the right to modify, at any time without notice, these statements, our services, products, and their warranty and performance specifications.